

# Stealth<sup>™</sup> 9200 Faceshield Goggle N Rated

Stealth<sup>™</sup> 9200 Faceshield Goggle N Rated / AGW010-603-000



# DESCRIPTION

A unique combination of indirect vented goggle and face protection with a sleek modern design. The Stealth<sup>™</sup> 9200 has been engineered to offer outstanding performance, comfort and looks.

# OPTIONS

Stealth<sup>™</sup> 9200 Faceshield Goggle N Rated (AGW010-603-000)

#### SAFETY STANDARDS

EN 166 • EN 170



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

#### SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect Scale Number 2C



Manufacturer's Trademark JSP Dagger



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles. В



Protection from Liquid Droplets 3



Resistance to Molten Metals and Hot Solids Helmets



(optional) 9



Product Weight 202g

## FEATURES



# Wraparound Lens

Large injection moulded spherical wraparound optically perfect lens for a clear field of vision. With anti-mist, anti-scratch and class 1 optics.



## Adjustable

Wide elastic headband with easy guick release clipping buckle makes it comfortable and suitable for most head sizes.



<u>:</u>@:-

1.2

1

Т

4

Ν



# Comfort

Resistance to fogging (optional)

Low quality for exceptional use)

temperatures. (-5°C and +55°C) Optional

Ultra soft housing and dual injection frame provides a soft comfortable fit that moulds to fit almost any face shape.

LIGHT TRANSMISSION BREAKDOWN Lens Shade number

Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 - Medium quality for occasional use. 3 - Class 3 -

The letter T, immediately after the mechanical strength

symbol, authorises use for high speed particles at extreme

Protection from Large Dust Particles (up to 40 um grain size)

# **Moveable Faceshield**

Lighter than a standard faceshield, this polycarbonate model can be easily lifted out of the way when not in use.

# APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Agricultural	Airports
Construction and Infrastructure	Facilities Management
Food and Drink Manufacturing	Manufacturing
Mining, Aggregates and Quarrying	Rail and Tunnelling
Renewable, Wind and Solar Energy	Scaffolding and Roofing
Sole Trader	Utilities Contractors
RANGE	DOWNLOADS



Image Pack (ZIP)

doc-stealth-9200.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

