

# TECHNICAL DATA SHEET

## 1125 CLASSIC

### DESCRIPTION

General purpose safety helmet with a 6 point Terylene cradle and Brushed Nylon sweatband.

### SPECIFICATION

Code	Option	Weight
S03C*A	Full Peak Slip Ratchet Non Vented	362gm
S03E*F	Full Peak Slip Ratchet Vented	362gm
S03C*R	Full Peak Wheel Ratchet Non Vented	381gm
S03C*RF	Full Peak Wheel Ratchet Vented	381gm
S17*A	Reduced Peak Slip Ratchet Non Vented	340gm
Size	51 - 63cm	
Peak	Full (40mm) or Reduced (20mm)	

\* Insert colour code of helmet.

### MATERIALS


Shell	HDPE (High Density Polyethylene)
Cradle	6 Point Terylene webbing
Headband	LDPE (Low Density Polyethylene)
Sweatband	Brushed Nylon with 2mm foam

### COLOURS


	White	Blue	Yellow	Red	Orange	Green
Colour Code	W	B	Y	R	O	G
RAL	9010	5015	1018	3028	2003	6035
Pantone	White	660	108	1795	1505	357

Please note: the closest matching RAL colours are listed.


### CORPORATE BADGING



Front	
↔↕	50 x 40mm
↔↕	45 x 45mm



Sides	
↔	100mm
↕	30mm



Rear	
↔	100mm
↕	30mm



## EUROPEAN AND INTERNATIONAL STANDARDS WITH OPTIONS

Product	EN 397:2012 + A1:2012				Options outside the scope of EN 397		EN 50365:2002 (1000V a.c.) For use on low voltage insulations	ANSI/ISEA Z89.1-2014 Type 1			Options outside the scope of ANSI/ISEA	CSA/ CAN Z94.1-05 Type 1		Tested to the performance requirements of AS/NZS 1801:1997 Type 1
	Lateral Deformation (LD)	- 30°C (Low Temperature)	Molten Metal (MM)	440V a.c. (Electrical Resistance)	1000V a.c. (Electrical Resistance)	- 40°C (Low Temperature)		Class C (Conductive 0V a.c.)	Class E (20,000V a.c.)	- 30°C (Low Temperature)	- 40°C (Low Temperature)	Class C (Conductive 0V a.c.)	Class E (20,000V a.c.)	
Full Peak Slip Ratchet Non Vented S03C*A		✓	✓	✓	✓			✓						
Full Peak Slip Ratchet Vented S03E*F		✓												
Full Peak Wheel Ratchet Non Vented S03C*R		✓	✓	✓	✓			✓						
Full Peak Wheel Ratchet Vented S03C*RF		✓												
Reduced Peak Slip Ratchet Non Vented S17*A		✓	✓	✓	✓									

## ACCESSORIES

Face	S03C*A Combi compatible with Connect & Euro range of Face Protection (carriers and face screens), S17*A compatible with Connect clips. S03E*F compatible with Euro clips
Accessory Clips	S565 Euro and S570 Connect clip sets for fitting safety helmet accessories
Ear	Compatible with Centurion helmet mounted Scala XI S72CE and Scala X S71CE Ear Defenders (supplied with S570 Connect and S565 Euro accessory clips)
Sweatband	S31N Brushed Nylon Sweatband
Cradle with Slip Ratchet	S33/3 Terylene Cradle with Brushed Nylon Sweatband
Chinstrap	Combi slot (S03C): S30E 2 point elasticated Chinstrap and S30LY 4 point SecurePlus Chinstrap Euro slot (S03E): S30E 2 point elasticated Chinstrap

## PACKAGING AND MAINTENANCE

Packaging	20 per colour, box size 58.7 x 44.7 x 43.7cm. Box weight 8.32kg (Full Peak), 8.04kg (Reduced Peak)
Storage	Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C) May be stored in the dark for up to 5 years Do not store in direct/high heat or sunlight as this may distort the shell
Lifetime	The Centurion safety helmet has an in-use life of up to 5 years Excessive wear and tear can considerably reduce the lifespan of the product
Cleaning	Clean using warm soapy water and soft cloth
Disposal	Recycling is preferred when possible. Look out for the recycling symbol for material category